

Sealed Flooded Monoblock Series

Tubular Positive Deep Cycle MF Battery

<p>TERMINAL(mm) Screw Type</p>	Dimensions(mm)									
	Length :	506 mm (19.92 inch)								
<p>BATTERY LAYOUT</p>	Width :	180 mm (7.09 inch)								
	Height :	210 mm (8.27 inch)								
	T. Height :	250 mm (9.84 inch)								
	Nominal Voltage :	12V								
	Capacity (5HR) :	96Ah/10.2V								
	Capacity (20HR) :	120Ah/10.5V								
	Cycle Use Chrg :	14.8-15.0V, <25A								
	Standby Use Chrg:	13.50-13.80, <25A								
	Cell Weight Filled :	40.6 kg								
	Cell Weight Dry :	29.5 kg								
Type of POS Plate :	Tubular Type									
Container Material :	PP Resin									
Storage :	< 3 months at 5-30 °C									
Size of Terminal :	M8									
Life Cycle (80%DOD) :	1250 cycles									
Life Cycle (30%DOD) :	2800 cycles									
Dchg. Time	DURATION OF DISCHARGE									
Amps.	15min.	30min.	1hr.	2hr.	3hr.	4hr.	5hr.	8hr.	10hr.	20hr.
	109	87.0	56.0	39.0	29.0	24.0	20.0	13.3	11.1	6.0

