

Motive Power Lead Acid Traction Battery

Battery Type		Rated Capacity(Ah)		Overall Dimension(mm)				Weight(kg)		Post Q'ty
		5hr	6hr	L	W	H	TH	DRY	WET	
VCA	180	180	-	109	158	295	328	9.5	12	2
	216	216	-	109	158	295	328	11.8	14.8	2
	238	238	-	141	158	295	328	12.8	16	2
	252	252	-	125	158	295	328	13.5	17	2
	288	288	-	141	158	295	328	15.7	19.5	2
	324	324	-	157	158	295	328	17.5	22	2
VCC	360	360	-	173	158	295	328	21	24.5	2
	120	120	-	61	158	328	361	6.6	8.2	2
	160	160	-	77	158	328	361	8.7	10.8	2
	200	200	-	93	158	328	361	10.5	13.5	2
	240	240	-	109	158	328	361	12.5	16	2
	280	280	-	125	158	328	361	14.8	18.6	2
VCD	320	320	-	141	158	328	361	17.2	21.5	2
	360	360	-	157	158	328	361	19	24	2
	400	400	-	173	158	328	361	21.5	27	2
	6	280	-	125	158	348	381	13.6	17.1	2
	8	360	-	141	158	348	381	19	24	2
	12	516	-	241	158	348	381	27.7	34.8	2
VCDH	150	150	170	61	158	395	428	9.2	11.5	2
	3A	165	-	61	158	393	426	10.1	12.6	2
	200	200	-	77	158	395	428	10.4	13.2	2
	48N	216	-	33	158	393	426	11.2	14.2	2
	250	250	-	93	158	395	428	12.5	16.5	2
	270	250	270	109	158	395	428	12.6	17	2
VCE	300	300	-	109	158	395	428	15	19.6	2
	320	320	-	125	158	374	407	16	20.9	2
	350	350	-	125	158	395	428	17.4	22.6	2
	360	360	-	125	158	374	407	17.9	23.2	2
	400	400	-	141	158	395	428	19.7	25.5	2
	450	450	-	157	158	395	428	23.2	29.5	2/4
VCI	500	500	-	173	158	395	428	24.6	32	2/4
	550	550	-	185	158	395	428	27.2	34.5	4
	600	600	-	204	158	395	428	29.5	37.5	4
	175	175	-	61	158	409	442	8.9	11	2
	232	232	-	77	158	409	442	11.5	14.5	2
	290	290	-	93	158	409	442	14.3	17.8	2
VCH	350	350	-	109	158	409	442	17.2	21.5	2
	400	400	-	125	158	409	442	20.2	25	2
	460	460	-	141	158	409	442	22.5	28	2/4
	520	520	-	157	158	409	442	25.7	32	2/4
	580	580	-	173	158	409	442	28.4	35.5	2/4
	630	630	-	185	158	409	442	30.5	38.5	4
VCI	700	700	-	204	158	409	442	34	42.5	4
	180	180	-	61	158	453	486	9.8	12.3	2
	240	240	-	77	158	453	486	13	16.2	2
	300	300	-	93	158	453	486	15.4	19.5	2
	360	360	-	109	158	453	486	18.5	23.5	2
	420	420	-	125	158	453	486	21.4	27	2/4
VCF	480	480	-	141	158	453	486	24	30.5	2/4
	540	540	-	157	158	453	486	26.5	34	2/4
	600	600	-	173	158	453	486	29	38	2/4
	660	660	-	185	158	453	486	31.2	40.5	4
		715	-	204	158	453	486	34	44	4

Design and specification are changed without notice.
Please confirm by contacting to us before you place an order.



ADDRESS: A 701-1 Digital Empire, 387 Simin-Daero, Dongan-Gu, Anyang-Si, Gyeonggi-Do, Korea #431- 804 TEL: (+82-31) 8086-7610/1 FAX: (+82-31) 8086-7612 E-Mail:ukb@ukbkorea.com Homepage: www.ukbkorea.com

Motive Power Lead Acid Traction Battery

Battery Type		Rated Capacity(Ah)		Overall Dimension(mm)				Weight(kg)		Post Q'ty
		5hr	6hr	Length	Width	Container's Height	Total Height	DRY	WET	
VCE	737	720	737	204	158	453	486	34.2	44.3	4
	715	660	715	237	158	453	486	31.6	43.5	4
	720	720	770	237	158	453	486	34.4	45.9	4
	740	740	-	237	158	453	486	35.2	46.4	4
	800	800	-	237	158	453	486	37.3	48.5	4
	880	840	880	237	158	453	486	39	49.9	4
	850	850	-	237	158	453	486	39.4	50.2	4
	3A 201/210	210	-	61	158	490	523	11	13.8	2
VCF	268/280	280	-	77	158	490	523	13.8	17.5	2
	280	280	-	90	158	490	523	14	18.5	2
	320	320	-	90/93	158	490	523	16.6	21.4	2
	335	335	-	93	158	490	523	16.9	21.7	2
	350	350	-	109	158	490	523	17	22.5	2
	6A	390	-	109	158	490	523	18.9	25	2
	400/420	420	-	109	158	490	523	20	25.5	2
	490	490	-	125	158	490	523	24	30.5	2/4
	545	545	-	141	158	490	523	25.2	34	2/4
	630	630	-	157	158	490	523	29	38	4
	10A	650	-	173	158	490	523	29.9	39.2	4
	700	700	-	173	158	490	523	33.5	42.2	4
VCH	3A	300	-	61	158	698	731	16	20.5	2
	4S	360	-	71	158	698	731	18.2	23	2
	150/160	160	-	45	158	519	552	8.7	10.8	2
	220 / 3A / 230	230	-	61	158	519	552	12.8	16	2
VCI	288/300	300	-	77	158	519	552	15.5	19.6	2
	335	300	335	90	158	519	552	16	20.5	2
	4	312	-	90	158	519	552	16.6	21.3	2
	365/375	375	-	93	158	519	552	19	24	2
	440	440	-	109	158	519	552	22	28	2/4
	546	546	-	125	158	519	552	26.2	34	2/4
	490	490	-	125	158	519	552	26	32.2	2/4
	505	505	-	125	158	519	552	26.2	32.5	2/4
	575/585	585	-	141	158	519	552	29.2	36.5	2/4
	595	546	595	141	158	519	552	26.5	34.2	2/4
	660	630	660	157	158	519	552	31	39	2/4
	710	670	710	185	158	519	552	33.2	42	4
	770	701	770	185	158	519	552	35	44	4
	845	845	-	185	158	519	552	38	48.7	4
	850	780	850	204	158	519	552	36	46.5	4
	11	858	-	204	158	519	552	38.5	49.4	4
	900	900	-	204	158	519	552	42	53	4
	990	990	-	221	158	519	552	48	60	4
	1080	1080	-	237	158	519	552	51.2	65.4	4
	VCJ	1200	1200	-	244	158	519	552	56	76
300		300	-	61	158	690	723	16	20	2
400		400	-	77	158	690	723	19.5	25	2
500		500	-	93	158	690	723	24	30	2
600		600	-	109	158	690	723	28.5	36	2/4
700		700	-	125	158	690	723	33	42	4
800		800	-	141	158	690	723	38	48	4
900		900	-	157	158	690	723	43	54	4
1000		1000	-	173	158	690	723	48	60	4
1100		1100	-	189	158	690	723	52	66	4
VGC	225	225	-	90	158	328	361	12.8	16	2
	520	520	-	185	158	328	361	24.9	31.2	2/4
VGD	415	415	-	125	158	393	426	20.2	25.9	2
	470	470	-	141	158	393	426	22.5	28.2	2
	485	485	-	141	158	408	441	23.2	29.1	2
	545	545	-	157	158	408	441	26.1	32.7	2
VGE	600	600	-	173	158	408	441	28.5	36	2/4
	245	245	-	77	158	453	486	13.6	17	2
VGF	220	220	-	61	158	488	521	12.8	16	2
	280	280	-	77	158	510	543	15	19	2
	370	370	-	93	158	488	521	18.7	23.6	2
	445	445	-	109	158	488	521	22.2	28.3	2
	530	530	-	125	158	488	521	25.7	33.1	2
	605	605	-	141	158	488	521	28.7	36.4	2/4
	730	730	-	173	158	488	521	34.4	43.8	4
	785	785	-	185	158	488	521	37.2	47.1	4
	865	865	-	204	158	488	521	41.3	51.9	4
	935	935	-	221	158	488	521	44.6	56.1	4
VGI	240	240	-	61	158	517	550	13.3	16.7	2
	285	285	-	77	158	517	550	14.2	18.8	2
	370	370	-	90	158	517	550	18.7	23.6	2
	470	470	-	109	158	517	550	23.5	29.9	2
	565	565	-	125	158	517	550	27.4	35.3	2
	645	645	-	141	158	517	550	31.7	39.9	2/4
	725	725	-	157	158	517	550	36.1	45.5	4
	1005	1005	-	221	158	517	550	48.2	60.3	4